


SCALE 1 : 1



9.53 [.375 in]

SPECIFICATIONS

Battery Type	3x AA (LR6) Cell Alkaline Batteries
Operating Temperature	-20° C to +50° C (-4 °F to 122 °F)
Maximum Operating pressure	2500 psi (172 bar)
O-Ring type and Size	2x 2-024/V90 (Viton O-ring)
Run time in Continuous Mode	100 + hours
Runtime in Pulse Mode	150 + hours
Open air signal strength	8 meters (26 feet)
In-Pipe signal strength	5 meters (14 feet)
Delrin Can part number	WT-AA-can

Note:

Open air test and in-pipe tests are carried out with a factory test receiver at full gain and external antenna connected. In-pipe test is performed by placing transmitter inside a 1/2" thick pipe.

Duracell - Procell ALKALINE batteries are strongly recommended in order to get the most run time on our transmitters.

Drawn by:	PM	
Revision Date:	2018-11-05	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF WAVETRAK ELECTRONICS LTD., ANY PRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION OF WAVETRAK ELECTRONICS IS PROHIBITED.		TITLE WT-AA-TR Spec Sheet
UNITS	REV	SHEET
mm [inches]	5	1